

Poz.	Średnica zewnętrzna, mm	Średnica wewnętrzna, mm	Grubość ścianki, mm	Gatunek stali	Długość
1	106	80	13	TP304/TP304L/1.4301/1.4307	3000-7000
2	170	140	15		3000-7000
3	160	132	14		3000-7000
4	132	90	21		3000-7000
5	125	100	12,5		3000-7000
6	80	50	15		4000-7000
7	180	156	12		3000-7000
8	100	80	10		4000-7000
9	150	125	12,5		3000-7000
10	140	112	14		3000-7000
11	71	56	7,5		4000-7000
12	132	106	13		3000-7000
13	56	40	8		4000-7000
14	56	36	10		4000-7000
15	180	150	15		3000-7000
16	80	63	8,5		4000-7000
17	112	90	11		3000-7000
18	160	112	24		3000-7000
19	224	180	22		3000-7000
20	140	100	20		3000-7000
21	125	90	17,5		3000-7000
22	90	71	9,5		4000-7000
23	63	50	6,5		4000-7000
24	140	90	25		3000-7000
25	71	45	13		4000-7000
26	63	45	9		4000-7000
27	150	106	22		3000-7000
28	90	63	13,5		4000-7000
29	63	40	11,5		4000-7000
30	112	80	16		3000-7000
31	118	90	14		3000-7000
32	100	56	22		3000-7000
33	106	71	17,5		3000-7000
34	170	118	26		3000-7000
35	125	71	27		3000-7000
36	118	95	11,5		3000-7000
37	150	95	27,5		3000-7000
38	132	90	21	TP316/TP316L/1.4401/1.4404	3000-7000
39	200	160	20	TP304/TP304L/1.4301/1.4307	3000-7000
40	160	120	20		3000-7000
41	160	120	20	TP316/TP316L/1.4401/1.4404	3000-7000
42	140	100	20		3000-7000
43	140	90	25		3000-7000